no.30 Natural stone, acid-resistant (sanded)



cleaning system without treatment end of construction

date	i	object
customer		address
representative		room classification

work	work process: select one work stage from each number								
	cleaning method	recommendations * chemical products	dosage	recommendations * pad / brush / mop / cloth	recommendations machine / tool	comments			
1	dry vacuum cleaning			Dust roller nozzle Neverclog filter without ring Filter bag with ring	Twinvac / Duovac / Silento /	large areas: sweeping			
2	dusting damp mopping			Masslinn 2000/Floorwit white Multi squeegee/	Balit Varifix / Balit/				
	cleaning without maintenance care pro	oduct (if coating follows							
3	wet mopping direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Micro-Mop Top/ Microsol mop/	Socar / Drewell				
3	scrubber drying direct method	Ecofloor V Reshine V Antiwax forte	0.5 - 1% 3 - 5% 2 - 5%	Microsol fibre pad/V ■ Pad green/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	green and black pad on hard stone only			
3	wet scrubbing and wet vacuuming	Reshine Antiwax forte	3 - 5% 2 - 5%	Microsol fibre pad/V ■ Pad green/	Monomatic I / Watertank Duovac /	heavily soiled			
4	stain removal	See cleaning instruct				if needed			
	cleaning with maintenance care (first								
5	wet mopping direct method	Redur	3%	Micro-Mop Top/ Microsol mop/	Socar / Drewell				
5	scrubber drying direct method	Redur	3%	Microsol fibre pad/ Pad red/	Duomatic / Laser Mambo / Samba Sprinter / iMatic				
5	spray cleaning full spray	Polyspray Elfspray	100% 100%	Pad red/ P Pad yellow/	Monomatic DS / Spray unit	after polishing			

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.30 Natural stone, acid-resistant (sanded)



maintenance cleaning			object			date		
			ad	ddress		customer		
work	process: select one work stage from	each nu	mber	room classif	ication		representative	
\bigcup	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/	
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping direct method		Ecofloor Reshine Alcosal	0.5 - 1% 1 - 2% 1 - 2%		Micro-Mop Top/ Mop Microbrush/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Ecofloor Reshine Libero	0.5 - 1% 1 - 2% 0.5 - 3%	V	Microsol fibre pad/ Pad red/ Pad blue/	Duomatic / Mambo / Samba Sprinter / iMatic	
3	polishing, vacuum polishing				В	Pad Blue Ice/ US pad yellow/	Monomatic HS / Suction ring Monomatic US /	after polishing
	cleaning with maintenance							
3	wet mopping direct method		Redur	1%		Micro-Mop Top/ Mop Variwet Mop Microbrush/	Wetbox system Socar / Drewell Variwet / B. Varifix	
3	scrubber drying direct method		Redur	1%	V	Microsol fibre pad/ Pad red/ Pad blue/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	
3	spray cleaning partial spray		Polyspray Elfspray	100% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	US spray cleaning partial spray		B US Restorer	100%	Р	US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

important: Sensitive or resistant against acid means against amidosulphuric acid

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.30 Natural stone, acid-resistant (sanded)



	interim cleaning				object		date customer	
work	work process: select one work stage from each number			room classifi			representative	
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix/ Balit/	
1	dry vacuum cleaning	ı []			V	Dust roller nozzle	Monovac / Scuba	large areas: sweeping
2	chewing gum removal		Karpfrost Karpotek	100%				if needed
	cleaning without maintenance							
3	wet mopping indirect method		Reshine G Antiwax forte	3 - 5% 2 - 5%		Micro-Mop Top/ Mop Microbrush/	Wetbox system Socar / Drewell	
3	scrubber drying indirect method		Reshine G Antiwax forte	3 - 5% 2 - 5%		Microsol fibre pad/ Pad blue/ Pad green/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	green and black pad on hard stone only
3	polishing, vacuum polishing				B B	Pad Blue Ice/ US pad yellow/	Monomatic HS / Suction ring Monomatic US /	after polishing
4	wet mopping direct method		Biosan	3%		Micro-Mop Top/ Mop Variwet	Socar / Drewell Wetcar / Drewell Variwet / B. Varifix	if needed, bad smell could be removed with
	cleaning with maintenance							
3	spray cleaning full spray		Polyspray Elfspray	100% 100%	Р	Pad red/ Pad yellow/	Monomatic DS / Spray unit	after polishing
3	spray cleaning full spray		B US Restorer	100%	P	US pad pink/ US pad yellow/	Monomatic US / Spray unit	after polishing

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled

no.30 Natural stone, acid-resistant (sanded)



	basic cleaning				objed	ct	date		
		address			customer				
	rk process: select one work stage from each number				icatio	n	representative		
	cleaning method	frequ ency	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping				В	Masslinn 2000/Floorwit white Synthetic fur	Balit Varifix / Balit/		
1	dry vacuum cleaning				V	Dust roller nozzle	Monovac / Scuba		
2	chewing gum removal		Karpfrost Karpotek	100%				if needed	
	cleaning without maintenance								
3	wet scrubbing and wet vacuuming		Antiwax forte G Rewit 2000 B Relino	30 - 50% 10 - 20% 20 - 50%	V	Microsol fibre pad/ Pad green/ Pad black/	Monomatic I / Watertank Duovac /		
3	scrubber drying indirect method		Antiwax forte G Rewit 2000 G Relino	30 - 50% 10 - 20% 20 - 50%	V	Microsol fibre pad/ Pad green/ Pad black/	Duomatic / Laser Mambo / Samba Sprinter / iMatic	2 m	
4	rinsing		pure water			Microsol fibre pad/ Pad green/	Monomatic I / Duovac / Duomatic / Laser	p	н7
5	stain removal		See cleaning instruc	ction no 41				if needed	
7	wet mopping indirect method		Biosan	3%		Micro-Mop Top / Mop Microbrush/ Mop Variwet	Wetbox system Socar / Drewell Variwet / B. Varifix	if needed, bad smell could be removed with	

Sensitive or resistant against acid means against amidosulphuric acid important: green and black pad on hard stone only

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.30 Natural stone, acid-resistant (sanded)



	protective treatment			object		date		
			a	ddress		customer		
work	process: select one work stage from each nu	mber	room classif	ication		representative		
	cleaning method	recommendations * chemical products	dosage	*	recommendations pad / brush / mop / cloth	recommendations machine / tool	comments	
1	dusting damp mopping				Masslinn 2000/Floorwit white	Balit Varifix / Balit/		
	coating							
2	impregnation	F Imprasol	100%		Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	apply first layer with care	<u>L</u>
	coating							
2	coating	Stoner	100%		Cover for Florfix Flat mop/	Florfix/ Drewell/ Buket plast 22l	1 - 3 thin layers	

important: if needed

Sensitive or resistant against acid means against amidosulphuric acid

before protective treatment: the floor must be perfectly stripped, thoroughly rinsed and completely dry!

Let dry protection treatment completely between the layers and before use

do not coat impregnated floors

Process treatement of protection: see descriptione of method

For initial cleaning with maintenance cleaner after protective treatment, see "initial cleaning".

^{*} basic treatment / structure: B: coated / C: waxed / D: oiled / E: sealed / F: untreated / G: maintenance care product / P: polishing / S: structured / V: heavily soiled



no.30 Natural stone, acid-resistant (sanded)



Information about the flooring



Wetrok AG cannot accept any liability for damages due to improper use.

For security information, see the safety data sheet at www.wetrok.ch.

Wear protection: gloves, safety goggles, work clothes

Follow the information and remarks on the label, product data sheet and material safety data sheet.

The product data sheet describes the product and gives information about its application, storage. See www.wetrok.ch

The recommended colours of pad and brushes consist to the actual wWetrok product range

Follow the special cleaning and care instructions of the floor manufacturer

The cleaning and care instructions are recommendations and suggestions and apply to floorings in object quality.



Hard types of stone, e.g. granite, queiss, quartzite and porphyry, are largely acid resistant.

Sensitive or resistant against acid means against amidosulphuric acid

The polish can be sensitive to acids or alkalines. Test in an inconspicuous place!

There must be no coating in the open air and in wet rooms. Danger of slipping!

Fats and oils can penetrate into the stone covering. Stain formation!

Soak the joints well or saturate them with an alkali cleaning solution before removing cement residue or limescale.



Natural stone is a 100% natural product consisting of minerals such as quartz, feldspar, calcite, selenite, hornblende or mica.

The colour and the appearance of the stone varies depending on its origin.

Distinguishing feature: natural stone acid-proof acid assay: apply a little basic sanitary cleaner to the stone covering, does not foam up.



Remove loose dirt before every cleaning, damp mop smooth floors and vacuum structured floors.

Cleaning agents and surface treatments may alter the appearance and properties of a floor's surface.

Test on an inconspicuous spot to find which product is suitable for your requirements.

Test beforehand on an inconspicuous spot to see if the cleaning agent or surface treatment damages the floor.

Dirt-trapping zones, incl. dirt-trapping mats (Wetrok Gardamat) in the entrance, at least 7m long, greatly reduce the amount of dirt tracked into the building.

If you have any questions, please don't hesitate to contact us.

For training courses, contact the Wetrok Academy, tel. +41 (0)43 255 51 43 or academy@wetrok.ch.

Wetrok AG Steinackerstrasse 62, CH-8302 Kloten, Tel +41 (0)43 255 51 51, info@wetrok.ch, www.wetrok.ch, www.wetrok.com