

VACUUM UNITS

CVAC 100 - Suction Unit medium power - CENTRALIZED VACUUM SYSTEMS



FOOD INDUSTRY



CEMENT WORKS AND CONSTRUCTION INDUSTRY



STEELWORKS AND FOUNDRIES



SAND BLASTING



SUCTION UNIT

| | | |
|---------------------------|--------|-------------|
| Voltage | V - Hz | 400 - 50 3~ |
| Power | kW | 7,5 |
| Max waterlift | mmH2O | 4.500 |
| Continuous water lift | mmH2O | 3.200 |
| Max air flow | m³/h | 750 |
| Suction inlet | mm | 100 |
| Noise level (EN ISO 3744) | dB(A) | 74 |



VOLUME

| | | |
|------------|----|------------|
| Dimensions | cm | 89x78x124h |
|------------|----|------------|

- ✓ Standard equipped with an electrical box with star delta start, LOC/REM control, pressure relief valve and noise buffering cover.



SUCTION UNIT

Suction is developed by a powerful side channel blower with direct coupling between the fan and the motor and no transmission system, making it completely maintenance free and fit for continuous duty.



OPTIONALS

- ✓ Additional silencer
- ✓ Safety cartridge Hepa H14 52.000cm²
- ✓ Inverter