

INDUSTRIAL VACUUM CLEANERS

W2 AIR 14V - Air operated vacuum cleaner for powders, liquids and solids - AIR POWERED



FOOD INDUSTRY



CHEMICAL-PHARMACEUTICAL



METALWORKING



SAND BLASTING



✓ 100% steel construction.

✓ Maintenance free Venturi suction unit.



SUCTION UNIT

Air supply	lt/min	1458
Air supply pressure	bar	6
Ø Air supply hose	mm	12
Max waterlift	mmH2O	3.700
Max air flow	m³/h	300
Suction inlet	mm	50
Noise level (EN ISO 3744)	dB(A)	78



FILTER UNIT

Filter Type		Star
Surface - Diameter	cm²-mm	20.000 - 420
Material - Efficiency	IEC 60335-2-69	Polyester - L
Cleaning system		Manual



COLLECTION UNIT

Collection tank		Steel
Discharge system		Roll-out container
Capacity	lt.	40



VOLUME

Dimensions	cm	63 x 57 x 108h
Weight	kg	43



SUCTION UNIT

Suction is developed by two Venturi compressed air generators which are protected inside a solid steel casing. Special noise buffers reduce noise level to work safety standards.



FILTER UNIT

The polyester star filter with large filtration surface placed inside the filter chamber ensures protection from dust and avoids filter clogging.



COLLECTION UNIT

The steel container has an easily detachable container for quick disposal of suctioned material.