

W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

INDUSTRIAL VACUUM CLEANERS



- ✓ ACD classification for vacuuming combustible dust in non-classified zones

Suction unit

Voltage	V - Hz	230 - 50/60 1~
Usage area		Ordinary location
EX category		CE ACD
Power	kW	2 x 1,1 bypass
Max waterlift	mmH2O	2.460
Max air flow	m3/h	360
Noise level (EN ISO 3744)	dB(A)	76

Filtering Unit

Primary filter		Star
Surface - Diameter	cm ² -mm	20.000 - 420
Cleaning system		Manual
Filtration efficiency		M ANT
Primary filter		Standard
Filter class		

Collection unit

Capacity	lt	40
Collection tank		Painted

Encumbrances

Dimensions	cm	63x57x116h
Weight	kg	40

APPLICATIONS:



All data mentioned in this document may change without notice.
Tutti i dati in questo documento potrebbero variare senza preavviso.

www.dupuyvacuums.com
info@dupuy.it

W2 ACD – ACD industrial vacuum cleaner for non-continuous applications in non-ATEX zones

INDUSTRIAL VACUUM CLEANERS

SUCTION UNIT

FILTERING UNIT

Inside the steel filter chamber is the antistatic polyester pocket filter, which protects the suction unit and prevents the risk of sparks due to static energy build-up. An absolute filter (99.995% of 0.18 micron, Class H) is included to ensure the retention of the finest dust and the purity of the exhaust air.

COLLECTION UNIT

The steel container is equipped with a quick release system that allows for quick disposal of the vacuumed material.