


# WD 3000 industrial wet and dry vacuum cleaner

INDUSTRIAL VACUUMS



- ✓ Accessories included, ideal for cleaning professionals.
- ✓ 100% steel construction.
- ✓ Simultaneous vacuuming of dust, liquids and solids.
- ✓ Liquid level monitored by a floating device to stop when the container is full.
- ✓ Tilting container for easy emptying.

## Suction Unit

Power supply	V - Hz	230 - 50 ~ 1
Power	kW	2 x 1,1
Maximum depression	mmH2O	2.400
Maximum air flow rate	m3/h	360
Nozzle	mm	50
Noisiness (EN ISO 3744)	dB(A)	78

## Filter Unit

Primary filter		Sack
Surface area - diameter	cm <sup>2</sup> -mm	5.000 - 420
Filter media - class	IEC 60335-2-69	Polyester L
Cleaning system		Handbook

## Collection unit

Capacity	lt	60
Float		Mechanic
Collection system		Tipping container

## Encumbrances

Dimensions	cm	62x60x100h
Weight	kg	32

APPLICATIONS:  General housekeeping  Food, chemical and pharmaceutical industry



All data mentioned in this document may change without notice.  
Tutti i dati in questo documento potrebbero variare senza preavviso.

[www.dupuyvacuums.com](http://www.dupuyvacuums.com)  
[info@dupuy.it](mailto:info@dupuy.it)

# WD 3000 industrial wet and dry vacuum cleaner

INDUSTRIAL VACUUMS

## **SUCTION UNIT**

---

Suction is generated by two carbon brush by-pass motors activated by independent switches located on a solid metal head, soundproofed with sound-absorbing material.

## **FILTER UNIT**

---

The polyester bag filter, placed inside the filter chamber, guarantees a large filtering surface area and high resistance to dust passage and clogging.

## **COLLECTION UNIT**

---

The vacuumed material is collected in a steel hopper container with an electro-pneumatically controlled swing door for quick discharge.